





Technology Request;

- 1.Outlook;Noburr,nohurt.
- 2.Electronic performance;
 - a.Insulotion resistance;Above DC500V/100MΩ;
 - b.Endur voiage;AC500V at 1 minute
 - c.Contact resistance;Under 30mΩ
- 3.Insertion force & withdrawal force;0.3-3kgf
- 4.Salt spray test;24H
- 5.Meet RoHS.
- 6.Remark * is important specification

4	管	C3604	Ni 40-120u
3	带尾弹圈	C5191	Ni 40-120u
2	针	C3604	Ni 40-120u
1	PLASTIC	LCP	Black
NO	PART	MATERIAL	PLATING

KQSYCN

www.kqsycn.com 科晴实业

400-092-6568

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF KQSYCN AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES	
>60	±0.60
30-60	±0.45
06-30	±0.35
0-6	±0.25
ANGLES	±1°

VIEW	
UNITS	mm
REV	A1
SHEET	1/1
DATE	2025. 08. 01

TITLE:	DC JACK $\varnothing 3.8 \times 1.35 \times 6.0-15.5$ 平胶带片
PART NO:	KQ-DC38135-H60

APPD	Li Jian
CHKD	Wan Yong
DRAW	Wan Yong