







BASE



COVER



## SPECIFICATIONS

Current Rating: 15 Amps @ 500V AC

Temperature Rating: -40 °C to 125°C

Insulator: PA9T , UL 94V-0 Black

Contacts: Brass

Finish: Nickel plating

Fuse Size: 5x20mm

# KQSYCN

www.kqsycn.com

400-092-6568


科晴实业

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF KQSYCN. AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

## TOLERANCES

>60 ±0.60  
30-60 ±0.45  
06-30 ±0.35  
0-6 ±0.25  
ANGLES ±1°

VIEW



UNITS

mm

REV

A1

SHEET

1/1

DATE

2025.08.09

TITLE:

保险丝座 5x20mm 双卡式 黑色底座  
袋装

PART NO:

KQ-S2006

APPD

Li Jian

CHKD

Wan Yong

DRAW

Wan Yong